

Producto: **Filtro Aster amb vàlvula lateral**

Product: **Aster Filter with lateral valve**



- . Construidos con resinas de poliéster y fibra de vidrio.
- . Excelente acabado.
- . Tapa en plástico de gran diámetro.
- . Montado con colectores de 1" y difusor de material plástico inalterable.
- . Equipado con manómetro, purga de agua manual, purga de aire automática y manual.
- . Conexiones para válvula selectora de seis vías con operaciones de filtración, lavado, enjuague, recirculación, vaciado y cerrado.
- . Presión máxima de trabajo: 2,5 Kg/cm2.

- . Made of polyester resins and glass fibre.
- . Excellent finish.
- . Plastic lid large diameter.
- . Fitted with 1" collector arms and diffuser made from unplasticised.
- . Fitted with pressure gauge, manual water drain cock, automatic and manual air vent cock.
- . Connections to multiport valve with six positions filter, backwash, rinse, recirculate, waste and closed.
- . Maximum working pressure of 2,5 Kg/cm2

	TABLA DE CARACTERÍSTICAS CHARACTERISTICS TABLE	Rev.01 Año/Year:2008 Pág./Page 2 / 5 ESP / ENG
---	---	---

Producto: **Filtro Aster amb vàlvula lateral**

Product: **Aster Filter with lateral valve**

CARACTERÍSTICAS / CHARACTERISTICS

Tabla 1	Filtro Aster 2,5 Kg/cm2 Aster Filter 2,5 Kg/cm2					
Código <i>Code</i>	00497	00498	19781	32706	00499	21071
Ø (mm)	350	450	500	550	600	650
Conexión (mm) <i>Connections (inch)</i>	1 ½"					
Velocidad de filtración (m3/h/m2) <i>Filtering velocity (m3/h/m2)</i>	50					
Sup. Filtración (m2) <i>Filtration Area (m2)</i>	0,096	0,159	0,196	0,238	0,283	0,332
Caudal (m³/h) <i>Flow (m³/h)</i>	5	8	9	11,5	14	15
Presión servicio (kg) <i>Working pressure (bar)</i>	2,5					
Carga arena (0,4-0,8mm) <i>Sand (0,4-0,8mm)</i>	50	70	90	110	125	200
Peso Neto (kg) <i>Net weight (kg)</i>	10	18	20	23	25	26
Piscina (m3) <i>Swimming Pool (m3)</i>	40	64	72	92	112	120

	TABLA DE CARACTERÍSTICAS CHARACTERISTICS TABLE	Rev.01 Año/Year:2008 Pág./Page 3 / 5 ESP / ENG
---	---	---

Producto: **Filtro Aster con válvula lateral**

Product: **Aster Filter with lateral valve**

CARACTERÍSTICAS / CHARACTERISTICS

Tabla 2	Filtro Aster 2,5 Kg/cm2 Aster Filter 2,5 Kg/cm2					
Código Code	28479	00500	40964	00501	08133	40965
Ø (mm)	680	750	800	900	900	950
Conexión (mm) Connections (inch)	1 ½"	2"		2 ½"	2"	2 ½"
Velocidad de filtración (m3/h/m2) Filtering velocity (m3/h/m2)	50					
Sup. Filtración (m2) Filtration Area (m2)	0,363	0,442	0,503	0,636	0,636	5/7
Caudal (m³/h) Flow (m³/h)	18	21	25	30	30	35
Presión servicio (kg) Working pressure (bar)	2,5					
Carga arena (0,4-0,8mm) Sand (0,4-0,8mm)	210	305	325	510	515	545
Peso Neto (kg) Net weight (kg)	28	33	40	51	50	65
Piscina (m3) Swimming Pool (m3)	144	168	200	240	240	280

	TABLA DE CARACTERÍSTICAS CHARACTERISTICS TABLE	Rev.01 Año/Year:2008 Pág./Page 4 / 5 ESP / ENG
---	---	---

Producto: **Filtro Aster con válvula lateral**

Product: **Aster Filter with lateral valve**

EMBALAGE / PACKAGING

Model MODELO	Box dimension / Dimensiones (m)	Volume (m³) Volumen (m³)
00497	0,39x0,39x0,76	0,11
00498	0,52x0,52x0,78	0,21
19781	0,56x0,56x0,85	0,26
32706	0,56x0,56x0,85	0,26
00499	0,66x0,66x0,86	0,37
21071	0,7x0,7x0,89	0,43
28479	0,7x0,7x0,89	0,43
00500	0,8x0,8x0,93	0,6
40964	0,8x0,8x0,93	0,6
00501 / 08133	0,98x0,98x1,3	1,25
40965	0,98x0,98x1,3	1,25

Código	Ø	D (mm)	H (mm)	M (mm)	N (mm)	K (mm)
00497	350	350	780	420	295	1 ½"
00498	450	450	795	430	305	
19781	500	500	805	415	290	
32706	550	575	825	455	330	
00499	600	600	850	455	330	
21071	650	650	905	495	370	
28479	680	680	915	525	400	
00500	750	750	985	555	325	2"
40964	800	815	960	590	360	
00501	900	900	1050	660	390	2 ½"
08133	900	900	1050	635	365	2"
40965	950	965	1050	670	400	2 ½"

